



## HP ProLiant SL390s G7 Intel® 5520 Socket B (LGA 1366) 4U ررف (U) أسود, الرمامدة



العلامة التجارية : HP

رمز المنتج: 612228-B21

اسم المنتج : ProLiant SL390s G7

HP ProLiant SL390s G7 4U Left Half Tray Node Server

HP ProLiant SL390s G7. ررفانق اللوحة الررفسفة: Intel® 5520, مقفس المعالج, Socket B (LGA 1366), فئة المعالج, القصى: 48 UDIMM القصى: 192 جفبافاف, ذاكرة RDIMM ذاكرة, 4GB, GB المدعومة: 16 سعات DIMM وحدات Intel. جفبافاف, أجام سوافاف الفزفن المدعومة: "2.5", واجهاف سوافاف الفزفن المدعومة: تسلسلف مرفق الحد الافصى من الذاكرة لبطافاف الفاشافة: 64 مفا باف. نوع واجهة. HP Smart Array B110i: جهاز الففكم فف الفزفن مفا باف فاففة, فقفنة كابلاف 10,100,1000 الشبكة: إفرنف سرفق, إفرنف عفبافف, معدلاف نقل بفافاف الشبكة الملفة مفا باف فاففة: 1000 BASE-T, 1000BASE-TX, 100BASE-TX, 10BASE-T

Processor		Network	
Motherboard chipset *	Intel® 5520	Ethernet LAN data rates	10,100,1000 Mbit/s
Processor socket *	Socket B (LGA 1366)	Copper ethernet cabling technology	1000BASE-T, 1000BASE-TX, 100BASE-TX, 10BASE-T
Processor family	Intel	<b>Ports &amp; interfaces</b>	
Number of processors supported *	2	USB 2.0 ports quantity *	3
Supported processor frequency (max)	3.6 GHz	Ethernet LAN (RJ-45) ports *	2
Compatible processor series	Intel® Xeon®	VGA (D-Sub) ports quantity	1
Intel Xeon series	E5500, E5600, L5600, X5600	Serial ports quantity	1
<b>Memory</b>		<b>Expansion slots</b>	
Number of DIMM slots *	12	PCI Express slots version	2.0
Supported DIMM module capacities	16GB, 4GB	PCI Express x8 slots	1
Maximum RDIMM memory	192 GB	PCI Express x16 slots	8
Maximum UDIMM memory	48 GB	<b>Features</b>	
Supported RDIMM clock speeds	800,1066,1333 MHz	Optical drive type	✗
Supported UDIMM clock speeds	800,1066,1333 MHz	Compatible operating systems	Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESX
ECC	✓	<b>Design</b>	
<b>Storage</b>		Chassis type *	Rack (4U)
Number of storage drives supported *	8	Product colour	Black, Grey
Storage drive sizes supported	2.5"	<b>Power</b>	
Supported storage drive interfaces	Serial Attached SCSI (SAS), Serial ATA	AC input voltage	90 - 264 V
Storage controller	HP Smart Array B110i	AC input frequency	47 - 63 Hz
RAID levels	0, 1, 10	<b>Operational conditions</b>	
<b>Graphics</b>		Operating temperature (T-T)	10 - 35 °C
Maximum graphics card memory	64 MB	Storage temperature (T-T)	-30 - 60 °C
<b>Network</b>		Operating relative humidity (H-H)	10 - 90%
Ethernet interface type	Fast Ethernet, Gigabit Ethernet	Storage relative humidity (H-H)	5 - 95%
<b>Other features</b>		Graphics card family	AMD

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-APR-2025. Prints or copies of Information are only valid on the printed Publication date