![DELL logo]

DELL PowerEdge T150 servidor 2 TB Rack (4U) Intel Xeon E E-2334 3,4 GHz 16 GB DDR4-SDRAM 300 W

Marca : DELL

Família do produto: PowerEdge

Código do produto: C2YCK

Nome do produto : T150

- No OS
- Intel Xeon E-2334 (8MB Cache, 3.4GHz)
- 16GB (3200MHz) DDR4-SDRAM (1 x 16) & 2000GB HDD
- iDRAC9 Basic 15G

Intel Xeon E-2334 (8MB Cache, 3.4GHz), 16GB DDR4-SDRAM (3200MHz), 2000GB HDD, LAN (Broadcom 5720), PERC H355, iDRAC9 Basic 15G, No OS

DELL PowerEdge T150 servidor 2 TB Rack (4U) Intel Xeon E E-2334 3,4 GHz 16 GB DDR4-SDRAM 300 W:

Ideal para primeiro servidor. Versátil, silencioso e fácil utilização.
Compacto Servidor torre de um soquete de fácil gerenciamento para você iniciar seus negócios de maneira eficiente, segura e performance nível empresarial.
DELL PowerEdge T150. Família do processador: Intel Xeon E, Freqüência do processador: 3,4 GHz, Modelo de processador: E-2334. Memória interna: 16 GB, Tipo de memória interna: DDR4-SDRAM, Configuração da memória (slots x dimensões): 1 x 16 GB. Capacidade total de armazenagem: 2 TB, Tamanho do disco rígido: 3.5", Interface do HD: SATA. Ethernet LAN, Tecnologia de cabeamento: 10/100/1000Base-T(X). Fonte de alimentação: 300 W. Tipo de chassi: Rack (4U)

Processor

Processor manufacturer *	Intel
Processor family *	Intel Xeon E
Processor model *	E-2334
Processor frequency *	3.4 GHz
Processor boost frequency	4.8 GHz
Processor cache	8 MB
Number of processors installed	1
Execute Disable Bit	✔
Idle States	✔

Memory

Internal memory *	16 GB
Internal memory type *	DDR4-SDRAM
Buffered memory type	Unregistered (unbuffered)
Memory slots	4x DIMM
ECC	✔
Memory clock speed	3200 MHz
Memory layout (slots x size)	1 x 16 GB
Memory data transfer rate	3200 MT/s
Maximum internal memory *	64 GB

Storage

Total storage capacity *	2 TB
Number of HDDs installed	1
HDD capacity	2 TB
HDD interface	SATA
HDD speed	7200 RPM
HDD size	3.5"
RAID support *	✘

Software

Operating system installed *	✘
Compatible operating systems *	Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server Citrix Hypervisor Canonical Ubuntu Server LTS

Processor special features

CPU configuration (max)	1
Enhanced Intel SpeedStep Technology	✔
Intel Virtualization Technology for Directed I/O (VT-d)	✔
Intel Trusted Execution Technology	✔
Intel VT-x with Extended Page Tables (EPT)	✔
Intel Software Guard Extensions (Intel SGX)	✔
Intel 64	✔
Intel Virtualization Technology (VT-x)	✔

Power

Power supply *	300 W
Number of main power supplies	1

Logistics data

Harmonized System (HS) code	84714100

Carbon footprint

Total carbon footprint (kg of CO2e)	2230
Total carbon emissions, standard deviation (kg of CO2e)	1010

Storage

Supported RAID controllers	PERC H355
Optical drive type *	✘

Graphics

On-board graphics card model	Not available

Network

LAN controller	Broadcom 5720
Ethernet LAN	✔
Cabling technology	10/100/1000Base-T(X)
Ethernet interface type	Gigabit Ethernet

Ports & interfaces

Ethernet LAN (RJ-45) ports *	2
USB 2.0 ports quantity	5
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
VGA (D-Sub) ports quantity	1
Serial ports quantity	1

Design

Chassis type *	Rack (4U)
Product colour	Black

Performance

Remote administration	iDRAC9 Basic 15G

Carbon footprint

Carbon emissions, manufacturing (kg of CO2e)	457
Carbon emissions, logistics (kg of CO2e)	139
Carbon emissions, energy usage (kg of CO2e)	1610
Carbon emissions, end-of-life (kg of CO2e)	21
Total carbon emissions, w/o use phase (kg of CO2e)	617
PAIA version	1.3.2, 2022

Weight & dimensions

Width	175 mm
Depth	453.8 mm
Height	360 mm
Weight	11.7 kg

Other features

Data transfer rate	6 Gbit/s
Bytes per sector	512n

5397184677445

7330381628566