## NEC PX700W Großraumprojektor 7000 ANSI Lumen DLP WXGA (1280x800) Schwarz

Marke : NEC

NEC

Artikel-Code: 60003828

Produktname : PX700W

DLP, 7000 Lumens, 1280 x 800, 2100:1, LAN, 2 x Mini D-sub 15-pin, HDMI, 2 x USB A, RJ-45, RS-232, 19.7kg, Nero

NEC PX700W. Projektorhelligkeit: 7000 ANSI Lumen, Projektion Technologie: DLP, native Auflösung des Projektors: WXGA (1280x800). Light source type: Lampe, Service life of light source: 2000 h, Service life of light source (economic mode): 2500 h. Fokus: Auto, Horizontal Linsenschwankung Range: -0,1 - 0,1°. Unterstützte Grafik-Auflösungen: 1280 x 800 (WXGA), 1920 x 1200 (WUXGA), 640 x 480 (VGA), Unterstützte Video-Modi: 1080i, 1080p, 480i, 480p, 576i, 576p, 720p. Serielle Schnittstelle: RS-232, USB-Stecker: USB Typ-A





| Projector   |   | Network  |  |
|---|---|--|--|
| Supported aspect ratios<br>Screen size compatibility *<br>Projection distance<br>Projector brightness *<br>Projector native resolution *<br>Contrast ratio (typical) *<br>Native aspect ratio *<br>Horizontal scan range<br>Vertical scan range<br>Keystone correction, horizontal<br>Keystone correction, vertical | 16:9, 16:10<br>1270 - 7620 mm (50 - 300")<br>0.8 - 54 m<br>7000 ANSI lumens<br>DLP<br>WXGA (1280x800)<br>2100:1<br>16:10<br>15 - 108 kHz<br>48 - 120 Hz<br>-40 - 40°<br>-30 - 30° | Wi-Fi *  | <ul> <li>Image: A second s</li></ul> |
|   |   | Storage  |  |
|   |   | Card reader integrated *   | ×  |
|   |   | Features<br>HDCP<br>On Screen Display (OSD)  | 1<br>1   |
|   |   | Noise level *<br>Plug and Play<br>Password protection<br>Certification   | 43 dB<br>✓<br>✓<br>CE; ErP; TÜV GS   |
| Matrix size   | 1.78 cm (0.7")  | Multimedia   |  |
| <b>Light source</b><br>Light source type *  | Lamp  | Image formats supported<br>Document formats supported  | JPG<br>PDF   |
| Service life of light source *  | 2000 h  | Design   |  |
| Service life of light source<br>(economic mode)<br>Lamp type<br>Lamp power  | 2500 h<br>AC HID<br>400 W   | Product type *<br>Product colour *<br>Placement  | Large venue projector<br>Black<br>Desktop, Ceiling   |
| Lamp power (economic mode)  | 400 W<br>320 W  | Display  |  |
| Lamps quantity  | 2 lamp(s)   | Built-in display *   | ×  |
| Lens system   |   | Power  |  |
| Focus *<br>Horizontal lens shift range<br>Number of optional lenses<br>supported  | Auto<br>-0.1 - 0.1°<br>7  | Power source *<br>Power consumption (typical) *<br>Power consumption (standby) *<br>Power consumption (network | AC<br>958 W<br>0.4 W   |
| Video   |   | standby)   | 18 W   |
| Full HD *<br>HD-Ready   | J<br>J  | Power consumption (economy<br>mode)<br>AC input voltage  | 753 W<br>100 - 240 V   |
| 3D *<br>Supported graphics resolutions  | ×<br>1280 x 800 (WXGA), 1920 x 1200<br>(WUXGA), 640 x 480 (VGA)   | AC input frequency   | 50 - 60 Hz   |

| Video  |  | Software  |   |
|--|--|---|---|
| Supported video modes1Supported video modes1Ports & interfacesDisplayPorts quantity1S-Video inputs quantity1USB 2.0 ports quantity2Serial interface type *RPC in (D-Sub)4VGA (D-Sub) ports quantity *3HDMI ports quantity *1USB connector type0BNC input ports5Composite video in *1 | 1080i, 1080p, 480i, 480p, 576i,<br>576p, 720p<br>1<br>1<br>1<br>2<br>RS-232<br>✓<br>3<br>1<br>USB Type-A<br>5<br>1 | Windows operating systems supported   | Windows 7 Enterprise, Windows 7<br>Enterprise x64, Windows 7 Home<br>Basic, Windows 7 Home Basic x64,<br>Windows 7 Home Premium,<br>Windows 7 Home Premium x64,<br>Windows 7 Professional, Windows 7<br>Professional x64, Windows 7<br>Starter, Windows 7 Starter x64,<br>Windows 7 Ultimate, Windows 7<br>Ultimate x64   |
|  |  | Weight & dimensions<br>Width<br>Depth<br>Height<br>Weight *<br>Packaging content  | 504 mm<br>516 mm<br>192 mm<br>19.7 kg   |
| AC (power) in<br><b>Network</b>  | 1  | Remote control included *<br>Remote control type  | ✓<br>IR   |
| Ethernet LAN *<br>Ethernet LAN (RJ-45) ports   | ✔<br>1   | Cables included<br>Quick start guide<br>Manual<br>Mounting brackets included<br><b>Technical details</b><br>Compliance certificates | AC<br><ul> <li>AC</li> <li>AC</li></ul> |

Logistics data

Other features RS-232 ports


Harmonized System (HS) code

Maximum analog resolution Maximum digital resolution 85286200

1920 x 1200 pixels

1920 x 1080 pixels

1



## 5028695610941

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.