

HP ProLiant SL390s G7 Intel® 5520 Socket B (LGA 1366) Rack (4U) Schwarz, Grau

Marke: HP Artikel-Code: 612228-B21

Produktname: ProLiant SL390s G7

HP ProLiant SL390s G7 4U Left Half Tray Node Server

HP ProLiant SL390s G7. Motherboard Chipsatz: Intel® 5520, Prozessorsockel: Socket B (LGA 1366), Prozessorfamilie: Intel. Unterstützte DIMM-Modulkapazitäten: 16GB, 4GB, Maximaler RDIMM Speicher: 192 GB, Maximaler UDIMM Speicher: 48 GB. unterstützte Speicherlaufwerksgrößen: 2.5", Unterstützte Speicherlaufwerk-Schnittstellen: Serial Attached SCSI (SAS), SATA, Storage controller: HP Smart Array B110i. Maximaler Grafikkartenspeicher: 64 MB. Ethernet Schnittstellen Typ: Schnelles Ethernet, Gigabit Ethernet, Ethernet LAN Datentransferraten: 10,100,1000 Mbit/s, Kupfer Ethernet Verkabelungstechnologie: 1000BASE-T, 1000BASE-TX, 100BASE-TX, 10BASE-T



D		Network	
Processor			
Motherboard chipset *	Intel® 5520	Ethernet LAN data rates	10,100,1000 Mbit/s
Processor socket * Processor family	Socket B (LGA 1366) Intel	Copper ethernet cabling technology	1000BASE-T, 1000BASE-TX, 100BASE-TX, 10BASE-T
Number of processors supported *	2	Ports & interfaces	
Supported processor frequency (max)	3.6 GHz	USB 2.0 ports quantity *	3
Compatible processor series	Intel® Xeon®	Ethernet LAN (RJ-45) ports *	2
Intel Xeon series	E5500, E5600, L5600, X5600	VGA (D-Sub) ports quantity	1
Memory		Serial ports quantity	1
Number of DIMM slots * Supported DIMM module capacities	12 16GB, 4GB	Expansion slots	
		PCI Express slots version	2.0
Maximum RDIMM memory	192 GB	PCI Express x8 slots	1
Maximum UDIMM memory	48 GB	PCI Express x16 slots	8
Supported RDIMM clock speeds	800,1066,1333 MHz	Features	
Supported UDIMM clock speeds	800,1066,1333 MHz	Optical drive type	×
ECC Storage	✓	Compatible operating systems	Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server
	1		VMware ESX
Number of storage drives supported *	8	Design	
Storage drive sizes supported	2.5"	Chassis type *	Rack (4U)
Supported storage drive interfaces	Serial Attached SCSI (SAS), Serial	Product colour	Black, Grey
Storage controller	ATA HP Smart Array B110i	Power	
•			
RAID levels	•	AC input voltage	90 - 264 V
RAID levels	0, 1, 10	AC input voltage AC input frequency	90 - 264 V 47 - 63 Hz
Graphics	0, 1, 10		
	•	AC input frequency	
Graphics	0, 1, 10	AC input frequency Operational conditions	47 - 63 Hz
Graphics Maximum graphics card memory	0, 1, 10	AC input frequency Operational conditions Operating temperature (T-T)	47 - 63 Hz 10 - 35 °C
Graphics Maximum graphics card memory Network	0, 1, 10 64 MB	AC input frequency Operational conditions Operating temperature (T-T) Storage temperature (T-T)	47 - 63 Hz 10 - 35 °C -30 - 60 °C
Graphics Maximum graphics card memory Network	0, 1, 10 64 MB	AC input frequency Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	47 - 63 Hz 10 - 35 °C -30 - 60 °C 10 - 90%

