

## Allied Telesis AT-AR415S wired router

**Brand :** Allied Telesis

**Product code:** AT-AR415S

**Product name :** AT-AR415S

Secure Modular Router

Allied Telesis AT-AR415S wired router:

The AT-AR415S is a secure modular router offering performance, flexibility and security for small to medium-sized businesses. Packaged in a compact one-rack unit chassis, this versatile router provides five 10/100 Fast Ethernet interfaces. It supports a variety of Port Interface Cards (PICs).

Secure Modular VPN Router with 1 x 1/100 WAN ports, 4 x LAN 10/100Base-T ports, 1x PIC slot, 1x Async console.

Allied Telesis AT-AR415S. Network standard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ac, IEEE 802.3u, IEEE 802.3x, Data transfer rate: 10 Mbit/s. Supported network protocols: SNMP, HTTP. Security algorithms: 3DES, DES. Flash memory: 16 MB, Mean time between failures (MTBF): 90000 h, Certification: EN55022 A, FCC A, VCCI A, AS/NZS CISPR22 A, EN55024, UL60950, CAN/CSA-C22.2NO. 60950-00, EN60950,.... Weight: 1.75 kg



Network		Features	
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ac, IEEE 802.3u, IEEE 802.3x	Plug and Play	✓
Data transfer rate	10 Mbit/s	Mean time between failures (MTBF)	90000 h
Supports ISDN connection	✓	Certification	EN55022 A, FCC A, VCCI A, AS/NZS CISPR22 A, EN55024, UL60950, CAN/CSA-C22.2NO. 60950-00, EN60950, UL, cUL, TUV
Management features		Minimum processor	266 MHz
Quality of Service (QoS) support	✓	Minimum RAM	32 MB
Universal Plug and Play (UPnP)	✓	Design	
Ports & interfaces		LED indicators	✓
Ethernet LAN (RJ-45) ports *	4	Operational conditions	
Protocols		Operating temperature (T-T)	0 - 40 °C
DHCP client *	✓	Storage temperature (T-T)	-25 - 70 °C
DHCP server *	✓	Operating relative humidity (H-H)	5 - 95%
Supported network protocols	SNMP, HTTP	Weight & dimensions	
Security		Weight	1.75 kg
Security algorithms *	3DES, DES	Other features	
MAC address filtering	✓	Maximum data transfer rate	0.1 Gbit/s
VPN tunnels quantity	50	Dimensions (WxDxH)	305 x 190 x 45 mm
Packaging content		Compatible operating systems	Windows XP, 2000
Manual	✓	Connectivity technology	Wired
Quick start guide	✓	Connectivity LEDs	✓
User Guide on CD-ROM	✓	Mac compatibility	✗
Features			
Flash memory	16 MB		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-APR-2025. Prints or copies of Information are only valid on the printed Publication date