

HP ProLiant SL390s G7 Intel® 5520 Socket B (LGA 1366) Rack (4U) Black, Grey

Brand: HP Product code: 612228-B21

Product name: ProLiant SL390s G7

HP ProLiant SL390s G7 4U Left Half Tray Node Server

HP ProLiant SL390s G7. Motherboard chipset: Intel® 5520, Processor socket: Socket B (LGA 1366), Processor family: Intel. Supported DIMM module capacities: 16GB, 4GB, Maximum RDIMM memory: 192 GB, Maximum UDIMM memory: 48 GB. Storage drive sizes supported: 2.5", Supported storage drive interfaces: Serial Attached SCSI (SAS), SATA, Storage controller: HP Smart Array B110i. Maximum graphics card memory: 64 MB. Ethernet interface type: Fast Ethernet, Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s, Copper ethernet cabling technology: 1000BASE-T, 1000BASE-TX, 100BASE-TX, 100BASE-TX,



Processor		Network	
Motherboard chipset *	Intel® 5520	Ethernet LAN data rates	10,100,1000 Mbit/s
Processor socket * Processor family	Socket B (LGA 1366) Intel	Copper ethernet cabling technology	1000BASE-T, 1000BASE-TX, 100BASE-TX, 10BASE-T
Number of processors supported *	2	Ports & interfaces	
Supported processor frequency (max)	3.6 GHz	USB 2.0 ports quantity * Ethernet LAN (RI-45) ports *	3 2
Compatible processor series Intel Xeon series	Intel® Xeon® E5500, E5600, L5600, X5600	VGA (D-Sub) ports quantity Serial ports quantity	1
Memory		Expansion slots	-
Number of DIMM slots * Supported DIMM module capacities Maximum RDIMM memory Maximum UDIMM memory	12 16GB, 4GB 192 GB 48 GB	PCI Express x8 slots PCI Express x8 slots PCI Express x16 slots	2.0 1 8
Supported RDIMM clock speeds	800,1066,1333 MHz	Features	
Supported UDIMM clock speeds	800,1066,1333 MHz	Optical drive type	×
ECC Storage	/	Compatible operating systems	Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESX
Number of storage drives supported *	8	Design	
Storage drive sizes supported	2.5"	Chassis type *	Rack (4U)
Supported storage drive interfaces	Serial Attached SCSI (SAS), Serial	Product colour	Black, Grey
Storage controller	ATA HP Smart Array B110i	Power	
RAID levels	0, 1, 10	AC input voltage	90 - 264 V
Graphics	0, 2, 20	AC input frequency	47 - 63 Hz
Maximum graphics card memory	64 MB	Operational conditions	
J , , , , , , , , , , , , , , , , , , ,	טויו דט	Operating temperature (T-T)	10 - 35 °C
Network	5 . 5	Storage temperature (T-T)	-30 - 60 °C
Ethernet interface type	Fast Ethernet, Gigabit Ethernet	Operating relative humidity (H-H) Storage relative humidity (H-H)	10 - 90% 5 - 95%
		Other features	
		Graphics card family	AMD

