

HP ProLiant SL390s G7 Intel® 5520 Socket B (LGA 1366) Rack (4U) Black, Grey

Brand: HP Product code: 612228-B21

Product name: ProLiant SL390s G7

HP ProLiant SL390s G7 4U Left Half Tray Node Server

HP ProLiant SL390s G7. Chipset: Intel® 5520, Processor socket: Socket B (LGA 1366), Processor type: Intel. Supported DIMM module capacities: 16GB, 4GB, Maximum RDIMM memory: 192 GB, Maximum UDIMM memory: 48 GB. Storage drive sizes supported: 2.5", Supported storage drive interfaces: Serial Attached SCSI (SAS), SATA, Storage controller: HP Smart Array B110i. Maximum graphics card memory: 64 MB. Ethernet interface type: Fast Ethernet, Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s, Copper ethernet cabling technology: 1000BASE-T, 1000BASE-TX, 100BASE-TX, 10BASE-T



Processor		Network	
Motherboard chipset *	Intel® 5520	Ethernet LAN data rates	10,100,1000 Mbit/s
Processor socket * Processor family	Socket B (LGA 1366) Intel	Copper ethernet cabling technology	1000BASE-T, 1000BASE-TX, 100BASE-TX, 10BASE-T
Number of processors supported *	2	Ports & interfaces	
Supported processor frequency (max)	3.6 GHz	USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports *	3 2
Compatible processor series Intel Xeon series	Intel® Xeon® E5500, E5600, L5600, X5600	VGA (D-Sub) ports quantity Serial ports quantity	1
Memory		,	1
Number of DIMM slots * Supported DIMM module capacities Maximum RDIMM memory Maximum UDIMM memory Supported RDIMM clock speeds	12 16GB, 4GB 192 GB 48 GB 800,1066,1333 MHz	Expansion slots PCI Express slots version PCI Express x8 slots PCI Express x16 slots	2.0 1 8
		Features	
Supported UDIMM clock speeds	800,1066,1333 MHz	Optical drive type	×
ECC Storage	*	Compatible operating systems	Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESX
Number of storage drives supported *	8	Design	
Storage drive sizes supported	2.5" Serial Attached SCSI (SAS), Serial ATA HP Smart Array B110i	Chassis type *	Rack (4U)
Supported storage drive interfaces		Product colour	Black, Grey
Storage controller		Power	
RAID levels	0, 1, 10	AC input voltage AC input frequency	90 - 264 V 47 - 63 Hz
Graphics		Operational conditions	
Maximum graphics card memory	64 MB	Operating temperature (T-T)	10 - 35 °C
Network		Storage temperature (T-T)	-30 - 60 °C
Ethernet interface type	Fast Ethernet, Gigabit Ethernet	Operating relative humidity (H-H) Storage relative humidity (H-H)	10 - 90% 5 - 95%
		Other features	

