

HP ProLiant SL390s G7 Intel® 5520 Socket B (LGA 1366) Bastidor (4U) Negro, Gris

Marca : HP Código del producto: 612228-B21

Nombre del producto: ProLiant SL390s G7

HP ProLiant SL390s G7 4U Left Half Tray Node Server

HP ProLiant SL390s G7. Chipset de tarjeta madre: Intel® 5520, Socket de procesador: Socket B (LGA 1366), Familia de procesador: Intel. Capacidades de módulo DIMM soportadas: 16GB, 4GB, memoria RDIMM máximo: 192 GB, Memoria máxima UDIMM: 48 GB. Tamaños de almacenamiento en disco soportados: 2.5", Interfaces de disco de almacenamiento soportados: Serial Attached SCSI (SAS), SATA, Controlador de almacenamiento: HP Smart Array B110i. Memoria máxima de adaptador de gráficos: 64 MB. Tipo de interfaz ethernet: Ethernet rápido, Gigabit Ethernet, Ethernet LAN, velocidad de transferencia de datos: 10,100,1000 Mbit/s, Tecnología de cableado ethernet de cobre: 1000BASE-T, 1000BASE-TX, 10BASE-TX, 10BASE-T



Processor		Network	
Motherboard chipset * Processor socket * Processor family	Intel® 5520 Socket B (LGA 1366) Intel	Ethernet LAN data rates Copper ethernet cabling technology	10,100,1000 Mbit/s 1000BASE-T, 1000BASE-TX, 100BASE-TX, 10BASE-T
Number of processors supported *	2	Ports & interfaces	
Supported processor frequency (max) Compatible processor series Intel Xeon series	3.6 GHz Intel® Xeon® E5500, E5600, L5600, X5600	USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports * VGA (D-Sub) ports quantity Serial ports quantity	3 2 1 1
Memory		Expansion slots	
Number of DIMM slots * Supported DIMM module capacities Maximum RDIMM memory Maximum UDIMM memory Supported RDIMM clock speeds	12 16GB, 4GB 192 GB 48 GB 800,1066,1333 MHz 800,1066,1333 MHz	PCI Express slots version PCI Express x8 slots PCI Express x16 slots	2.0 1 8
		Features	
Supported UDIMM clock speeds ECC		Optical drive type Compatible operating systems	X Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server
Storage		compatible operating systems	VMware ESX
Number of storage drives supported *	8	Design	
Storage drive sizes supported	2.5" Serial Attached SCSI (SAS), Serial ATA HP Smart Array B110i 0, 1, 10	Chassis type * Product colour	Rack (4U) Black, Grey
Supported storage drive interfaces		Power	
Storage controller RAID levels		AC input voltage AC input frequency	90 - 264 V 47 - 63 Hz
Graphics		Operational conditions	
Maximum graphics card memory	64 MB	Operating temperature (T-T)	10 - 35 °C
Network Ethernet interface type	Fast Ethernet, Gigabit Ethernet	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-30 - 60 °C 10 - 90% 5 - 95%
		Other features	
		Graphics card family	AMD

