Allied Telesis AT-AR415S langallinen reititin

Tuotemerkki : Allied Telesis Tuotekoodi: AT-AR415S

Tuotteen nimi: AT-AR415S

Allied Telesis AT-AR415S. Verkkostandardit: IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ac, IEEE 802.3u, IEEE 802.3x, Tiedonsiirtonopeus: 10 Mbit/s. Tuetut verkkoprotokollat: SNMP, HTTP. Tietoturva-algoritmit: 3DES, DES. Flash-muisti: 16 MB, Keskimääräinen vikaantumisaika: 90000 h, Sertifiointi: EN55022 A, FCC A, VCCI A, AS/NZS CISPR22 A, EN55024, UL60950, CAN/CSA-C22.2NO. 60950-00, EN60950,.... Paino: 1,75 kg





Network		Features	
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE	Plug and Play	✓
Data transfer rate	802.3ac, IEEE 802.3u, IEEE 802.3x 10 Mbit/s	Mean time between failures (MTBF)	90000 h
Supports ISDN connection		Certification	EN55022 A, FCC A, VCCI A, AS/NZS CISPR22 A, EN55024, UL60950, CAN/CSA-C22.2NO. 60950-00, EN60950, UL, cUL,TUV
Management features			
Quality of Service (QoS) support	✓	Minimum processor	266 MHz
Universal Plug and Play (UPnP)	✓	Minimum RAM	32 MB
Ports & interfaces		Design	
Ethernet LAN (RJ-45) ports *	4	LED indicators	✓
Protocols		Operational conditions	
DHCP client *	✓	Operating temperature (T-T)	0 - 40 °C
DHCP server *	1	Storage temperature (T-T)	-25 - 70 °C
Supported network protocols	SNMP, HTTP	Operating relative humidity (H-H)	5 - 95%
Security		Weight & dimensions	
Security algorithms *	3DES, DES	Weight	1.75 kg
MAC address filtering	✓	Other features	
VPN tunnels quantity	50	Maximum data transfer rate	0.1 Gbit/s
Packaging content		Dimensions (WxDxH)	305 x 190 x 45 mm
Manual	✓	Compatible operating systems Connectivity technology	Windows XP, 2000 Wired
Quick start guide	✓	Connectivity LEDs	✓
User Guide on CD-ROM	✓	Mac compatibility	X
Features			
Flash memory	16 MB		

