## Allied Telesis AT-AR415S Routeur connecté

Marque : Allied Telesis Code produit: AT-AR415S

Nom du produit : AT-AR415S

Allied Telesis AT-AR415S. Standards réseau: IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ac, IEEE 802.3u, IEEE 802.3x, Taux de transfert de données: 10 Mbit/s. Protocoles réseau pris en charge: SNMP, HTTP. Algorithme de sécurité soutenu: 3DES, DES. Mémoire flash: 16 Mo, Temps moyen entre pannes: 90000 h, Certification: EN55022 A, FCC A, VCCI A, AS/NZS CISPR22 A, EN55024, UL60950, CAN/CSA-C22.2NO. 60950-00, EN60950,.... Poids: 1,75 kg





Network		Features	
	IEEE 802.1D, IEEE 802.1Q, IEEE	Plug and Play	<b>✓</b>
Networking standards *	802.3ac, IEEE 802.3u, IEEE 802.3x	Mean time between failures (MTBF)	90000 h
Data transfer rate	10 Mbit/s		EN55022 A, FCC A, VCCI A, AS/NZS
Supports ISDN connection	<b>✓</b>	Certification	CISPR22 A, EN55024, UL60950, CAN/CSA-C22.2NO. 60950-00.
Management features			EN60950, UL, cUL, TUV
Quality of Service (QoS) support	✓	Minimum processor	266 MHz
Universal Plug and Play (UPnP)	✓	Minimum RAM	32 MB
Ports & interfaces		Design	
Ethernet LAN (RJ-45) ports *	4	LED indicators	✓
Protocols		Operational conditions	
DHCP client *	<b>✓</b>	Operating temperature (T-T)	0 - 40 °C
DHCP server *	<b>✓</b>	Storage temperature (T-T)	-25 - 70 °C
Supported network protocols	SNMP, HTTP	Operating relative humidity (H-H)	5 - 95%
Security		Weight & dimensions	
Security algorithms *	3DES, DES	Weight	1.75 kg
MAC address filtering	<b>✓</b>	Other features	
VPN tunnels quantity	50	Maximum data transfer rate	0.1 Gbit/s
Packaging content		Dimensions (WxDxH)	305 x 190 x 45 mm
Manual	<b>✓</b>	Compatible operating systems  Connectivity technology	Windows XP, 2000 Wired
Quick start guide	<b>✓</b>	Connectivity LEDs	✓
User Guide on CD-ROM	✓	Mac compatibility	×
Features			
Flash memory	16 MB		

