



## HP ProLiant SL390s G7 Intel® 5520 Socket B (LGA 1366) Rack (4 U) Noir, Gris

Marque : HP

Code produit: 612228-B21

Nom du produit : ProLiant SL390s G7



HP ProLiant SL390s G7 4U Left Half Tray Node Server

HP ProLiant SL390s G7. Carte mère chipset: Intel® 5520, Socket de processeur (réceptacle de processeur): Socket B (LGA 1366), Famille de processeur: Intel. Tailles de DIMM supportées: 16GB, 4GB, Mémoire RDIMM maximum: 192 Go, Mémoire UDIMM maximum: 48 Go. Tailles de disque de stockage pris en charge: 2.5", Interfaces de lecteur de stockage prises en charge: Série Attachée SCSI (SAS), SATA, Contrôleur de stockage: HP Smart Array B110i. Taille de la mémoire vidéo: 64 Mo. Type d'interface Ethernet: Fast Ethernet, Gigabit Ethernet, LAN Ethernet : taux de transfert des données: 10,100,1000 Mbit/s, Technologie de câblage Ethernet cuivre: 1000BASE-T, 1000BASE-TX, 100BASE-TX, 10BASE-T

| Processor                            |                                        | Network                            |                                                                                 |
|--------------------------------------|----------------------------------------|------------------------------------|---------------------------------------------------------------------------------|
| Motherboard chipset *                | Intel® 5520                            | Ethernet LAN data rates            | 10,100,1000 Mbit/s                                                              |
| Processor socket *                   | Socket B (LGA 1366)                    | Copper ethernet cabling technology | 1000BASE-T, 1000BASE-TX, 100BASE-TX, 10BASE-T                                   |
| Processor family                     | Intel                                  | Ports & interfaces                 |                                                                                 |
| Number of processors supported *     | 2                                      | USB 2.0 ports quantity *           | 3                                                                               |
| Supported processor frequency (max)  | 3.6 GHz                                | Ethernet LAN (RJ-45) ports *       | 2                                                                               |
| Compatible processor series          | Intel® Xeon®                           | VGA (D-Sub) ports quantity         | 1                                                                               |
| Intel Xeon series                    | E5500, E5600, L5600, X5600             | Serial ports quantity              | 1                                                                               |
| Memory                               |                                        | Expansion slots                    |                                                                                 |
| Number of DIMM slots *               | 12                                     | PCI Express slots version          | 2.0                                                                             |
| Supported DIMM module capacities     | 16GB, 4GB                              | PCI Express x8 slots               | 1                                                                               |
| Maximum RDIMM memory                 | 192 GB                                 | PCI Express x16 slots              | 8                                                                               |
| Maximum UDIMM memory                 | 48 GB                                  | Features                           |                                                                                 |
| Supported RDIMM clock speeds         | 800,1066,1333 MHz                      | Optical drive type                 | ✗                                                                               |
| Supported UDIMM clock speeds         | 800,1066,1333 MHz                      | Compatible operating systems       | Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESX |
| ECC                                  | ✓                                      | Design                             |                                                                                 |
| Storage                              |                                        | Chassis type *                     | Rack (4U)                                                                       |
| Number of storage drives supported * | 8                                      | Product colour                     | Black, Grey                                                                     |
| Storage drive sizes supported        | 2.5"                                   | Power                              |                                                                                 |
| Supported storage drive interfaces   | Serial Attached SCSI (SAS), Serial ATA | AC input voltage                   | 90 - 264 V                                                                      |
| Storage controller                   | HP Smart Array B110i                   | AC input frequency                 | 47 - 63 Hz                                                                      |
| RAID levels                          | 0, 1, 10                               | Operational conditions             |                                                                                 |
| Graphics                             |                                        | Operating temperature (T-T)        | 10 - 35 °C                                                                      |
| Maximum graphics card memory         | 64 MB                                  | Storage temperature (T-T)          | -30 - 60 °C                                                                     |
| Network                              |                                        | Operating relative humidity (H-H)  | 10 - 90%                                                                        |
| Ethernet interface type              | Fast Ethernet, Gigabit Ethernet        | Storage relative humidity (H-H)    | 5 - 95%                                                                         |
|                                      |                                        | Other features                     |                                                                                 |
|                                      |                                        | Graphics card family               | AMD                                                                             |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-APR-2025. Prints or copies of Information are only valid on the printed Publication date