

NEC PX700W 7000 ANSI lumens מקרן לאירועים גדולים DLP WXGA (1280x800) שחור

מותג : NEC

קוד מוצר: 60003828

שם דגם : PX700W



NEC PX700W. 7000. בהירות: מקרן , בהירות: ANSI lumens, טכנולוגיית הקרנה, DLP, מקרן של המקרן, רזולוציית מקרנית של המקרן, WXGA (1280x800). סוג מקור תאורה: מנורה, חיי השירות של מקור התאורה: 2000 שעות, חיי השירות של מקור התאורה (מצב). (1280x800). סוג מקור תאורה: מנורה, חיי השירות של מקור התאורה: 2000 שעות, חיי השירות של מקור התאורה (מצב). (1280x800). 800 x חסכוני): 2500 שעות. פוקוס: אוטומטי, טווח הסטה אופקי לעדשה: 0.1° - 0.1°. רזולוציות גרפיקה נתמכות: 1280 (WXGA), 1920 x 1200 (WUXGA), 640 x 480 (VGA), 1080i, 1080p, 480i, 480p, 576i, 576p, 720p. סוג ממשק טורי. RS-232, מחבר, USB: USB Type-A

| | | | |
|--|---|-------------------------------------|-----------------------|
| Projector | | Network | |
| Supported aspect ratios | 16:9, 16:10 | Wi-Fi * | ✓ |
| Screen size compatibility * | 1270 - 7620 mm (50 - 300") | Storage | |
| Projection distance | 0.8 - 54 m | Card reader integrated * | ✗ |
| Projector brightness * | 7000 ANSI lumens | Features | |
| Projection technology * | DLP | HDCP | ✓ |
| Projector native resolution * | WXGA (1280x800) | On Screen Display (OSD) | ✓ |
| Contrast ratio (typical) * | 2100:1 | Noise level * | 43 dB |
| Native aspect ratio * | 16:10 | Plug and Play | ✓ |
| Horizontal scan range | 15 - 108 kHz | Password protection | ✓ |
| Vertical scan range | 48 - 120 Hz | Certification | CE; ErP; TÜV GS |
| Keystone correction, horizontal | -40 - 40° | Multimedia | |
| Keystone correction, vertical | -30 - 30° | Image formats supported | JPG |
| Matrix size | 1.78 cm (0.7") | Document formats supported | PDF |
| Light source | | Design | |
| Light source type * | Lamp | Product type * | Large venue projector |
| Service life of light source * | 2000 h | Product colour * | Black |
| Service life of light source (economic mode) | 2500 h | Placement | Desktop, Ceiling |
| Lamp type | AC HID | Display | |
| Lamp power | 400 W | Built-in display * | ✗ |
| Lamp power (economic mode) | 320 W | Power | |
| Lamps quantity | 2 lamp(s) | Power source * | AC |
| Lens system | | Power consumption (typical) * | 958 W |
| Focus * | Auto | Power consumption (standby) * | 0.4 W |
| Horizontal lens shift range | -0.1 - 0.1° | Power consumption (network standby) | 18 W |
| Number of optional lenses supported | 7 | Power consumption (economy mode) | 753 W |
| Video | | AC input voltage | 100 - 240 V |
| Full HD * | ✓ | AC input frequency | 50 - 60 Hz |
| HD-Ready | ✓ | | |
| 3D * | ✗ | | |
| Supported graphics resolutions | 1280 x 800 (WXGA), 1920 x 1200 (WUXGA), 640 x 480 (VGA) | | |

| Video | | Software | |
|------------------------------|--|-------------------------------------|--|
| Supported video modes | 1080i, 1080p, 480i, 480p, 576i, 576p, 720p | | Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64 |
| Ports & interfaces | | Windows operating systems supported | |
| DisplayPorts quantity | 1 | | |
| S-Video inputs quantity | 1 | | |
| USB 2.0 ports quantity | 2 | | |
| Serial interface type * | RS-232 | | |
| PC in (D-Sub) | ✓ | | |
| VGA (D-Sub) ports quantity * | 3 | | |
| HDMI ports quantity * | 1 | | |
| USB connector type | USB Type-A | | |
| BNC input ports | 5 | | |
| Composite video in * | 1 | | |
| DVI port * | ✗ | | |
| AC (power) in | ✓ | | |
| Network | | Weight & dimensions | |
| Ethernet LAN * | ✓ | Width | 504 mm |
| Ethernet LAN (RJ-45) ports | 1 | Depth | 516 mm |
| | | Height | 192 mm |
| | | Weight * | 19.7 kg |
| | | Packaging content | |
| | | Remote control included * | ✓ |
| | | Remote control type | IR |
| | | Cables included | AC |
| | | Quick start guide | ✓ |
| | | Manual | ✓ |
| | | Mounting brackets included | ✓ |
| | | Technical details | |
| | | Compliance certificates | RoHS |
| | | Logistics data | |
| | | Harmonized System (HS) code | 85286200 |
| | | Other features | |
| | | RS-232 ports | 1 |
| | | Maximum analog resolution | 1920 x 1200 pixels |
| | | Maximum digital resolution | 1920 x 1080 pixels |



5028695610941

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-APR-2025. Prints or copies of Information are only valid on the printed Publication date