

HP ProLiant SL390s G7 Intel® 5520 Socket B (LGA 1366) Stalak (4U) Crno, Sivo

Brend: HP Kod proizvoda: 612228-B21

Ime proizvoda: ProLiant SL390s G7

HP ProLiant SL390s G7 4U Left Half Tray Node Server

HP ProLiant SL390s G7. Čipset matične ploče: Intel® 5520, Utor za procesor: Socket B (LGA 1366), Porodica procesora: Intel. Podržane veličine DIMM memorije: 16GB, 4GB, Maksimalna RDIMM memorija: 192 GB, Maksimalna UDIMM memorija: 48 GB. Podržane veličine pogona za pohranu: 2.5", Podržana sučelja pogona za pohranu: Serijski spojevi SCSI (SAS), SATA, Kontroler pohrane: HP Smart Array B110i. Maksimalna memorija grafičke kartice: 64 MB. Vrsta Ethernet sučelja: Brzi Ethernet, Gigabit Ethernet, brzine prijenosa podataka putem Ethernet LANa: 10,100,1000 Mbit/s, Tehnologija bakrenih ethernet kabela: 1000BASE-T, 1000BASE-TX, 100BASE-TX, 10BASE-T



Processor		Network	
Motherboard chipset * Processor socket * Processor family	Intel® 5520 Socket B (LGA 1366) Intel	Ethernet LAN data rates Copper ethernet cabling technology	10,100,1000 Mbit/s 1000BASE-T, 1000BASE-TX, 100BASE-TX, 10BASE-T
Number of processors supported *	2	Ports & interfaces	
Supported processor frequency (max) Compatible processor series Intel Xeon series	3.6 GHz Intel® Xeon® E5500, E5600, L5600, X5600	USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports * VGA (D-Sub) ports quantity Serial ports quantity	3 2 1
Memory		Expansion slots	
Number of DIMM slots * Supported DIMM module capacities Maximum RDIMM memory Maximum UDIMM memory	12 16GB, 4GB 192 GB 48 GB	PCI Express slots version PCI Express x8 slots PCI Express x16 slots	2.0 1 8
Supported RDIMM clock speeds	800,1066,1333 MHz	Features	
Supported UDIMM clock speeds	800,1066,1333 MHz	Optical drive type	x
ECC Storage	/	Compatible operating systems	Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESX
Number of storage drives supported	8	Design	
Storage drive sizes supported	2.5"	Chassis type *	Rack (4U)
Supported storage drive interfaces	Serial Attached SCSI (SAS), Serial ATA	Product colour	Black, Grey
Storage controller	HP Smart Array B110i	Power	
RAID levels	•	AC input voltage	90 - 264 V
	0, 1, 10	AC input frequency	47 - 63 Hz
Graphics	0, 1, 10	AC input frequency	47 - 63 Hz
Graphics Maximum graphics card memory	64 MB	Operational conditions	
-			47 - 63 Hz 10 - 35 °C -30 - 60 °C
Maximum graphics card memory		Operational conditions Operating temperature (T-T)	10 - 35 °C
Maximum graphics card memory Network	64 MB	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	10 - 35 °C -30 - 60 °C 10 - 90%

