

HP ProLiant SL390s G7 Intel® 5520 Socket B (LGA 1366) Armadio (4U) Nero, Grigio

Marchio: HP Codice prodotto: 612228-B21

Nome del prodotto: ProLiant SL390s G7

HP ProLiant SL390s G7 4U Left Half Tray Node Server

HP ProLiant SL390s G7. Chipset scheda madre: Intel® 5520, Presa per processore: Socket B (LGA 1366), Famiglia processore: Intel. Capacità del modulo DIMM supportate: 16GB, 4GB, memoria massima RDIMM: 192 GB, memoria massima UDIMM: 48 GB. Dimensioni dei dispositivi di archivio supportati: 2.5", Interfacce dell'unità di archiviazione supportate: Serial Attached SCSI (SAS), SATA, Unità di controllo di archiviazione: HP Smart Array B110i. Memoria massima adattatore grafico: 64 MB. Tipo di interfaccia Ethernet: Fast Ethernet, Gigabit Ethernet, Velocità trasferimento Ethernet LAN: 10,100,1000 Mbit/s, Tecnologia Ethernet su cavi in rame: 1000BASE-T, 1000BASE-TX, 100BASE-TX, 10BASE-T



Processor		Network	
Motherboard chipset * Processor socket * Processor family	Intel® 5520 Socket B (LGA 1366) Intel	Ethernet LAN data rates Copper ethernet cabling technology	10,100,1000 Mbit/s 1000BASE-T, 1000BASE-TX, 100BASE-TX, 10BASE-T
Number of processors supported *	2	Ports & interfaces	
Supported processor frequency (max) Compatible processor series	3.6 GHz Intel® Xeon®	USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports *	3 2
Intel Xeon series	E5500, E5600, L5600, X5600	VGA (D-Sub) ports quantity Serial ports quantity	1
Memory		Expansion slots	1
Number of DIMM slots * Supported DIMM module capacities Maximum RDIMM memory Maximum UDIMM memory Supported RDIMM clock speeds	12 16GB, 4GB 192 GB 48 GB 800,1066,1333 MHz	PCI Express slots version	2.0
		PCI Express x8 slots	1
		PCI Express x16 slots	8
		Features	
Supported UDIMM clock speeds	800,1066,1333 MHz	Optical drive type	×
ECC Storage	•	Compatible operating systems	Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESX
Number of storage drives supported	8	Design	
Storage drive sizes supported	2.5" Serial Attached SCSI (SAS), Serial ATA HP Smart Array B110i 0, 1, 10	Chassis type *	Rack (4U)
Supported storage drive interfaces		Product colour	Black, Grey
Storage controller		Power	
RAID levels		AC input voltage	90 - 264 V
Graphics	· ·	AC input frequency	47 - 63 Hz
Maximum graphics card memory	64 MB	Operational conditions	
Network		Operating temperature (T-T)	10 - 35 °C
Ethernet interface type	Fast Ethernet, Gigabit Ethernet	Storage temperature (T-T) Operating relative humidity (H-H)	-30 - 60 °C 10 - 90%
		Storage relative humidity (H-H)	5 - 95%
		Other features	
		Graphics card family	AMD

