

## 

Brand: HP Product code: 612228-B21

Product name: ProLiant SL390s G7

HP ProLiant SL390s G7 4U Left Half Tray Node Server



Processor		Network	
Motherboard chipset *	Intel® 5520	Ethernet LAN data rates	10,100,1000 Mbit/s
Processor socket * Processor family	Socket B (LGA 1366) Intel	Copper ethernet cabling technology	1000BASE-T, 1000BASE-TX, 100BASE-TX, 10BASE-T
Number of processors supported *	2	Ports & interfaces	
Supported processor frequency (max)	3.6 GHz	USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports *	3 2
Compatible processor series Intel Xeon series	Intel® Xeon® E5500, E5600, L5600, X5600	VGA (D-Sub) ports quantity	1
	25500, 25000, 25000, X5000	Serial ports quantity	1
Memory		Expansion slots	
Number of DIMM slots * Supported DIMM module capacities Maximum RDIMM memory Maximum UDIMM memory Supported RDIMM clock speeds	12 16GB, 4GB 192 GB 48 GB 800,1066,1333 MHz	PCI Express slots version PCI Express x8 slots PCI Express x16 slots	2.0 1 8
		Features	
Supported UDIMM clock speeds	800,1066,1333 MHz	Optical drive type	×
ECC <b>Storage</b>	<b>*</b>	Compatible operating systems	Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESX
Number of storage drives supported *	8	Design	
Storage drive sizes supported	2.5"	Chassis type *	Rack (4U)
Supported storage drive interfaces	Serial Attached SCSI (SAS), Serial ATA HP Smart Array B110i	Product colour	Black, Grey
Storage controller		Power	
RAID levels	0, 1, 10	AC input voltage	90 - 264 V
	0, 1, 10	AC input frequency	47 - 63 Hz
Graphics	CAMP	Operational conditions	
Maximum graphics card memory	64 MB	Operating temperature (T-T)	10 - 35 °C
Network		Storage temperature (T-T)	-30 - 60 °C
Ethernet interface type	Fast Ethernet, Gigabit Ethernet	Operating relative humidity (H-H) Storage relative humidity (H-H)	10 - 90% 5 - 95%
		Other features	
		Graphics card family	AMD

