

DELL PowerEdge R250 server 2 TB Rack (1U) Intel Xeon E E-2314 2,8 GHz 8 GB DDR4-SDRAM 450 W

Merk : DELL

Productfamilie: PowerEdge

Artikelcode: 6V2CT

Productnaam : R250

- No OS

- Intel Xeon E-2314 (8MB Cache, 2.8GHz)

- 8GB (3200MT/s) DDR4-SDRAM (1 x 8) & 2000GB HDD

- iDRAC9, Express 15G

Intel Xeon E-2314 (8MB Cache, 2.8GHz), 8GB DDR4-SDRAM (3200MT/s), 2000GB HDD, LAN (Broadcom 5720), iDRAC9, Express 15G, 450W, No OS

DELL PowerEdge R250 server 2 TB Rack (1U) Intel Xeon E E-2314 2,8 GHz 8 GB DDR4-SDRAM 450 W:

Lever de meerwaarde van data

Bied betaalbare oplossingen voor veelvoorkomende zakelijke workloads en lever krachtige rekenkracht met een 1U rackserver op instapniveau.

DELL PowerEdge R250. Processorfamilie: Intel Xeon E, Frequentie van processor: 2,8 GHz, Processormodel: E-2314. Intern geheugen: 8 GB, Intern geheugentype: DDR4-SDRAM, Geheugenlayout: 1 x 8 GB. Totale opslagcapaciteit: 2 TB, HDD omvang: 3.5", HDD interface: SATA III. Ethernet LAN, Bekabelingstechnologie: 10/100/1000Base-T(X). Netvoeding: 450 W. Type behuizing: Rack (1U)

Processor Software Processor manufacturer * Intel Canonical® Ubuntu® Server LTS Citrix[®] Hypervisor Microsoft[®] Processor family * Intel Xeon E Windows Server® with Hyper-V Compatible operating systems * E-2314 Processor model * RedHat[®] Enterprise Linux SUSE[®] Processor frequency * 2.8 GHz Linux Enterprise Server VMware® **ESXi**® Processor boost frequency 4.5 GHz 8 MB Processor cache Processor special features Number of processors installed 1 CPU configuration (max) 1 Execute Disable Bit Enhanced Intel SpeedStep 1 Technology Idle States Intel Virtualization Technology for Memory Directed I/O (VT-d) Internal memory * 8 GB Intel Trusted Execution Technology 1 DDR4-SDRAM Internal memory type * Intel VT-x with Extended Page Tables (EPT) Buffered memory type Unregistered (unbuffered) Intel Software Guard Extensions Memory slots 4x DIMM (Intel SGX) ECC 1 Intel 64 Memory layout (slots x size) 1 x 8 GB Intel Virtualization Technology (VT-3200 MT/s Memory data transfer rate X) Maximum internal memory * 128 GB Power Storage Redundant power supply (RPS) × Total storage capacity * 2 TB support * Number of HDDs installed 1 Power supply * 450 W HDD capacity 2 TB Number of main power supplies 1 SATA III HDD interface Power cable length 2 m HDD speed 7200 RPM Power cable connector 1 C13 coupler HDD size 3.5" Power cable connector 2 C14 coupler Number of HDDs supported 4 Power cable current 10 A Supported HDD sizes 3.5"



| Storage | | Logistics data | |
|---|---------------------------|---|-------------|
| RAID support * | × | Harmonized System (HS) code | 84714100 |
| Hot-Plug support | ✓ | Carbon footprint | |
| Optical drive type * | × | Total carbon footprint (kg of CO2e) | 2100 |
| Graphics | | Total carbon emissions, standard deviation (kg of CO2e) | 935 |
| On-board graphics card model | Not available | Carbon emissions, manufacturing (kg of CO2e) | 505 |
| Network | | | |
| LAN controller | Broadcom 5720 | Carbon emissions, logistics (kg of CO2e) | 110 |
| Ethernet LAN Cabling technology | ✓ 10/100/1000Base-T(X) | Carbon emissions, energy usage (kg of CO2e) | 1470 |
| Ethernet interface type | Gigabit Ethernet | Carbon emissions, end-of-life (kg of CO2e) | 17 |
| Ports & interfaces | | Total carbon emissions, w/o use | 632 |
| Ethernet LAN (RJ-45) ports * | 2 | phase (kg of CO2e) | 052 |
| USB 2.0 ports quantity | 2 | PAIA version | 1.3.2, 2022 |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 1 | Weight & dimensions | |
| VGA (D-Sub) ports quantity | 1 | Width | 482 mm |
| Design | | Height | 42.8 mm |
| Chassis type * | Rack (1U) | Other features | |
| Product colour | Black | Data transfer rate | 6 Gbit/s |
| Rack mounting | | Bytes per sector | 512n |
| - | • | | |
| Performance | | | |
| Remote administration | iDRAC9, Express 15G | | |
| Software | | | |
| Operating system installed * | × | | |



5397184745762

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.