

NEC PX700W Projector voor grote zalen 7000 ANSI lumens DLP WXGA (1280x800) Zwart

Merk : NEC

Artikelcode: 60003828

Productnaam : PX700W



DLP, 7000 Lumens, 1280 x 800, 2100:1, LAN, 2 x Mini D-sub 15-pin, HDMI, 2 x USB A, RJ-45, RS-232, 19.7kg, Black

NEC PX700W. Projector helderheid: 7000 ANSI lumens, Projectietechnologie: DLP, Projector native resolution: WXGA (1280x800). Type lichtbron: Lamp, Levensduur van de lichtbron: 2000 uur, Levensduur van de lichtbron (besparingsmodus): 2500 uur. Focus: Auto, Horizontale lens verplaatsingsbereik: -0,1 - 0,1°. Ondersteunde grafische resoluties: 1280 x 800 (WXGA), 1920 x 1200 (WUXGA), 640 x 480 (VGA), Ondersteunde video-modi: 1080i, 1080p, 480i, 480p, 576i, 576p, 720p. Soort serieële aansluiting: RS-232, USB-connectortype: USB Type-A

| Projector | | Network | |
|--|---|-------------------------------------|-----------------------|
| Supported aspect ratios | 16:9, 16:10 | Wi-Fi * | ✓ |
| Screen size compatibility * | 1270 - 7620 mm (50 - 300") | | |
| Projection distance | 0.8 - 54 m | Storage | |
| Projector brightness * | 7000 ANSI lumens | Card reader integrated * | ✗ |
| Projection technology * | DLP | Features | |
| Projector native resolution * | WXGA (1280x800) | HDCP | ✓ |
| Contrast ratio (typical) * | 2100:1 | On Screen Display (OSD) | ✓ |
| Native aspect ratio * | 16:10 | Noise level * | 43 dB |
| Horizontal scan range | 15 - 108 kHz | Plug and Play | ✓ |
| Vertical scan range | 48 - 120 Hz | Password protection | ✓ |
| Keystone correction, horizontal | -40 - 40° | Certification | CE; ErP; TÜV GS |
| Keystone correction, vertical | -30 - 30° | Multimedia | |
| Matrix size | 1.78 cm (0.7") | Image formats supported | JPG |
| Light source | | Document formats supported | PDF |
| Light source type * | Lamp | Design | |
| Service life of light source * | 2000 h | Product type * | Large venue projector |
| Service life of light source (economic mode) | 2500 h | Product colour * | Black |
| Lamp type | AC HID | Placement | Desktop, Ceiling |
| Lamp power | 400 W | Display | |
| Lamp power (economic mode) | 320 W | Built-in display * | ✗ |
| Lamps quantity | 2 lamp(s) | Power | |
| Lens system | | Power source * | AC |
| Focus * | Auto | Power consumption (typical) * | 958 W |
| Horizontal lens shift range | -0.1 - 0.1° | Power consumption (standby) * | 0.4 W |
| Number of optional lenses supported | 7 | Power consumption (network standby) | 18 W |
| Video | | Power consumption (economy mode) | 753 W |
| Full HD * | ✓ | AC input voltage | 100 - 240 V |
| HD-Ready | ✓ | AC input frequency | 50 - 60 Hz |
| 3D * | ✗ | | |
| Supported graphics resolutions | 1280 x 800 (WXGA), 1920 x 1200 (WUXGA), 640 x 480 (VGA) | | |

| Video | | Software | |
|------------------------------|--|-------------------------------------|--|
| Supported video modes | 1080i, 1080p, 480i, 480p, 576i, 576p, 720p | | Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64 |
| Ports & interfaces | | Windows operating systems supported | |
| DisplayPorts quantity | 1 | | |
| S-Video inputs quantity | 1 | | |
| USB 2.0 ports quantity | 2 | | |
| Serial interface type * | RS-232 | | |
| PC in (D-Sub) | ✓ | | |
| VGA (D-Sub) ports quantity * | 3 | | |
| HDMI ports quantity * | 1 | | |
| USB connector type | USB Type-A | | |
| BNC input ports | 5 | | |
| Composite video in * | 1 | | |
| DVI port * | ✗ | | |
| AC (power) in | ✓ | | |
| Network | | Weight & dimensions | |
| Ethernet LAN * | ✓ | Width | 504 mm |
| Ethernet LAN (RJ-45) ports | 1 | Depth | 516 mm |
| | | Height | 192 mm |
| | | Weight * | 19.7 kg |
| | | Packaging content | |
| | | Remote control included * | ✓ |
| | | Remote control type | IR |
| | | Cables included | AC |
| | | Quick start guide | ✓ |
| | | Manual | ✓ |
| | | Mounting brackets included | ✓ |
| | | Technical details | |
| | | Compliance certificates | RoHS |
| | | Logistics data | |
| | | Harmonized System (HS) code | 85286200 |
| | | Other features | |
| | | RS-232 ports | 1 |
| | | Maximum analog resolution | 1920 x 1200 pixels |
| | | Maximum digital resolution | 1920 x 1080 pixels |



5028695610941

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-APR-2025. Prints or copies of Information are only valid on the printed Publication date