Allied Telesis AT-AR415S router

Merk: Allied Telesis Artikelcode: AT-AR415S

Productnaam: AT-AR415S

Allied Telesis AT-AR415S. Netwerkstandaard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ac, IEEE 802.3u, IEEE 802.3x, Overdrachtssnelheid: 10 Mbit/s. Ondersteunde netwerkprotocollen: SNMP, HTTP. Ondersteunde beveiligingsalgoritmen: 3DES, DES. Flash memory: 16 MB, Mean time between failures (MTBF): 90000 uur, Certificering: EN55022 A, FCC A, VCCI A, AS/NZS CISPR22 A, EN55024, UL60950, CAN/CSA-C22.2NO. 60950-00, EN60950,.... Gewicht: 1,75 kg





Network		Features	
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE	Plug and Play	✓
Data transfer rate	802.3ac, IEEE 802.3u, IEEE 802.3x 10 Mbit/s	Mean time between failures (MTBF)	90000 h
Supports ISDN connection	10 Mbit/S		EN55022 A, FCC A, VCCI A, AS/NZS CISPR22 A, EN55024, UL60950,
Management features	•	Certification	CAN/CSA-C22.2NO. 60950-00,
		•	EN60950, UL, cUL, TUV
Quality of Service (QoS) support	✓	Minimum processor	266 MHz
Universal Plug and Play (UPnP)	✓	Minimum RAM	32 MB
Ports & interfaces		Design	
Ethernet LAN (RJ-45) ports *	4	LED indicators	✓
Protocols		Operational conditions	
DHCP client *	1	Operating temperature (T-T)	0 - 40 °C
DHCP server *	✓	Storage temperature (T-T)	-25 - 70 °C
Supported network protocols	SNMP, HTTP	Operating relative humidity (H-H)	5 - 95%
Security		Weight & dimensions	
Security algorithms *	3DES, DES	Weight	1.75 kg
MAC address filtering	*	Other features	
VPN tunnels quantity	50	Maximum data transfer rate	0.1 Gbit/s
Packaging content		Dimensions (WxDxH)	305 x 190 x 45 mm
Manual	✓	Compatible operating systems Connectivity technology	Windows XP, 2000 Wired
Quick start guide	✓	Connectivity LEDs	√
User Guide on CD-ROM	✓	Mac compatibility	×
Features		· · · · · · · · · · · · · · · · · · ·	•
Flash memory	16 MB		

