



## DELL PowerEdge R250 serwer 2 TB Rack (1U) Intel Xeon E E-2314 2,8 GHz 8 GB DDR4-SDRAM 450 W

Marka : DELL

Rodzina produktu: PowerEdge Kod produktu: 6V2CT

Nazwa produktu : R250



DELL PowerEdge R250. Typ procesora: Intel Xeon E, Taktowanie procesora: 2,8 GHz, Model procesora: E-2314. Pamięć wewnętrzna: 8 GB, Typ pamięci wewnętrznej: DDR4-SDRAM, Układ pamięci: 1 x 8 GB. Całkowita pojemność przechowywania: 2 TB, Rozmiar HDD: 3.5", Interfejs HDD: SATA III. Przewodowa sieć LAN, Technologia okablowania: 10/100/1000Base-T(X). Zasilanie: 450 W. Obudowa: Rack (1U)



| Processor                      |                           | Software   |             |
|--------------------------------|---------------------------|--|-------------|
| Processor manufacturer *       | Intel                     | Compatible operating systems *<br>Canonical® Ubuntu® Server LTS<br>Citrix® Hypervisor Microsoft®<br>Windows Server® with Hyper-V<br>RedHat® Enterprise Linux SUSE®<br>Linux Enterprise Server VMware®<br>ESXi® |             |
| Processor family *             | Intel Xeon E              |  |             |
| Processor model *              | E-2314                    |  |             |
| Processor frequency *          | 2.8 GHz                   |  |             |
| Processor boost frequency      | 4.5 GHz                   |  |             |
| Processor cache                | 8 MB                      |  |             |
| Number of processors installed | 1                         |  |             |
| Execute Disable Bit            | ✓                         |  |             |
| Idle States                    | ✓                         |  |             |
| Memory                         |                           | Processor special features   |             |
| Internal memory *              | 8 GB                      | CPU configuration (max)  | 1           |
| Internal memory type *         | DDR4-SDRAM                | Enhanced Intel SpeedStep Technology  | ✓           |
| Buffered memory type           | Unregistered (unbuffered) | Intel Virtualization Technology for Directed I/O (VT-d)  | ✓           |
| Memory slots                   | 4x DIMM                   | Intel Trusted Execution Technology   | ✓           |
| ECC                            | ✓                         | Intel VT-x with Extended Page Tables (EPT)   | ✓           |
| Memory layout (slots x size)   | 1 x 8 GB                  | Intel Software Guard Extensions (Intel SGX)  | ✓           |
| Memory data transfer rate      | 3200 MT/s                 | Intel 64   | ✓           |
| Maximum internal memory *      | 128 GB                    | Intel Virtualization Technology (VT-x)   | ✓           |
| Storage                        |                           | Power  |             |
| Total storage capacity *       | 2 TB                      | Redundant power supply (RPS) support *   | ✗           |
| Number of HDDs installed       | 1                         | Power supply *   | 450 W       |
| HDD capacity                   | 2 TB                      | Number of main power supplies  | 1           |
| HDD interface                  | SATA III                  | Power cable length   | 2 m         |
| HDD speed                      | 7200 RPM                  | Power cable connector 1  | C13 coupler |
| HDD size                       | 3.5"                      | Power cable connector 2  | C14 coupler |
| Number of HDDs supported       | 4                         | Power cable current  | 10 A        |
| Supported HDD sizes            | 3.5"                      |  |             |

|   |                      |   |             |
|---|----------------------|---|-------------|
| <b>Storage</b>                                  |                      | <b>Logistics data</b>                                   |             |
| RAID support *                                  | ✗                    | Harmonized System (HS) code                             | 84714100    |
| Hot-Plug support                                | ✓                    | <b>Carbon footprint</b>                                 |             |
| Optical drive type *                            | ✗                    | Total carbon footprint (kg of CO2e)                     | 2100        |
| <b>Graphics</b>                                 |                      | Total carbon emissions, standard deviation (kg of CO2e) | 935         |
| On-board graphics card model                    | Not available        | Carbon emissions, manufacturing (kg of CO2e)            | 505         |
| <b>Network</b>                                  |                      | Carbon emissions, logistics (kg of CO2e)                | 110         |
| LAN controller                                  | Broadcom 5720        | Carbon emissions, energy usage (kg of CO2e)             | 1470        |
| Ethernet LAN                                    | ✓                    | Carbon emissions, end-of-life (kg of CO2e)              | 17          |
| Cabling technology                              | 10/100/1000Base-T(X) | Total carbon emissions, w/o use phase (kg of CO2e)      | 632         |
| Ethernet interface type                         | Gigabit Ethernet     | PAIA version  | 1.3.2, 2022 |
| <b>Ports &amp; interfaces</b>                   |                      | <b>Weight &amp; dimensions</b>                          |             |
| Ethernet LAN (RJ-45) ports *                    | 2                    | Width   | 482 mm      |
| USB 2.0 ports quantity                          | 2                    | Height  | 42.8 mm     |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 1                    | <b>Other features</b>                                   |             |
| VGA (D-Sub) ports quantity                      | 1                    | Data transfer rate                                      | 6 Gbit/s    |
| <b>Design</b>                                   |                      | Bytes per sector  | 512n        |
| Chassis type *                                  | Rack (1U)            |   |             |
| Product colour                                  | Black                |   |             |
| Rack mounting                                   | ✓                    |   |             |
| <b>Performance</b>                              |                      |   |             |
| Remote administration                           | iDRAC9, Express 15G  |   |             |
| <b>Software</b>                                 |                      |   |             |
| Operating system installed *                    | ✗                    |   |             |



5397184745762

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 13-APR-2025. Prints or copies of Information are only valid on the printed Publication date