

## HP ProLiant SL390s G7 Intel® 5520 Socket B (LGA 1366) Rek orman (4U) Crno, Sivo

Brand: HP Product code: 612228-B21

Product name: ProLiant SL390s G7

HP ProLiant SL390s G7 4U Left Half Tray Node Server

HP ProLiant SL390s G7. Skup čipova matične ploče: Intel® 5520, Podnožje procesora: Socket B (LGA 1366), Porodica procesora: Intel. Kapaciteti podržanih DIMM modula: 16GB, 4GB, Maksimalna RDIMM memorija: 192 GB, Maksimalna UDIMM memorija: 48 GB. Podržane veličine uređaja za skladištenje: 2.5", Podržani interfejsi uređaja za skladištenje: Serial Attached SCSI (SAS), SATA, Kontroler medija za čuvanje podataka: HP Smart Array B110i. Maksimalna memorija grafičkog adaptera: 64 MB. Tip Eternet interfejsa: Fast Ethernet, Gigabitni ethernet, Brzina prenosa podataka na Eternet LAN-u: 10,100,1000 Mbit/s, Tehnologija bakarnih kablova za eternet: 1000BASE-TX, 100BASE-TX, 10BASE-T



Processor		Network	
Motherboard chipset *	Intel® 5520	Ethernet LAN data rates	10,100,1000 Mbit/s
Processor socket * Processor family	Socket B (LGA 1366) Intel	Copper ethernet cabling technology	1000BASE-T, 1000BASE-TX, 100BASE-TX, 10BASE-T
Number of processors supported *	2	Ports & interfaces	
Supported processor frequency (max)	3.6 GHz	USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports *	3 2
Compatible processor series Intel Xeon series	Intel® Xeon® E5500, E5600, L5600, X5600	VGA (D-Sub) ports quantity Serial ports quantity	1 1
Memory		Expansion slots	
Number of DIMM slots * Supported DIMM module capacities Maximum RDIMM memory Maximum UDIMM memory	12 16GB, 4GB 192 GB 48 GB	PCI Express x8 slots PCI Express x8 slots PCI Express x16 slots	2.0 1 8
Supported RDIMM clock speeds	800,1066,1333 MHz	Features	
Supported UDIMM clock speeds	800,1066,1333 MHz	Optical drive type	×
ECC Storage	<b>*</b>	Compatible operating systems	Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESX
Number of storage drives supported *	8	Design	
Storage drive sizes supported	2.5" Serial Attached SCSI (SAS), Serial ATA HP Smart Array B110i	Chassis type *	Rack (4U)
Supported storage drive interfaces		Product colour	Black, Grey
Storage controller		Power	
RAID levels	0, 1, 10	AC input voltage AC input frequency	90 - 264 V 47 - 63 Hz
Graphics			47 03 112
Maximum graphics card memory	64 MB	Operational conditions	10. 25.00
Network		Operating temperature (T-T) Storage temperature (T-T)	10 - 35 °C -30 - 60 °C
Ethernet interface type	Fast Ethernet, Gigabit Ethernet	Operating relative humidity (H-H) Storage relative humidity (H-H)	10 - 90% 5 - 95%
Ethernet interface type	Fast Ethernet, Gigabit Ethernet		

