# Allied Telesis AT-AR415S дротовий маршрутизатор

**Виробник :** Allied Telesis

**Код продукту:** AT-AR415S

**Назва моделі :** AT-AR415S

Allied Telesis AT-AR415S. Стандарти мережі: IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ac, IEEE 802.3u, IEEE 802.3x, Швидкість передачі даних: 10 Мбіт/с. Підтримані мережеві протоколи: SNMP, HTTP. Алгоритми шифрування даних: 3DES, DES. Флеш-пам'ять: 16 МБ, Середній час напрацювання на відмову (MTBF): 90000 год., Сертифікація: EN55022 A, FCC A, VCCI A, AS/NZS CISPR22 A, EN55024, UL60950, CAN/CSA-C22.2NO. 60950-00, EN60950,.... Вага: 1,75 кг

| Network | |
|---|---|
| Networking standards * | IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ac, IEEE 802.3u, IEEE 802.3x |
| Data transfer rate | 10 Mbit/s |
| Supports ISDN connection | ✔ |
| **Management features** | |
| Quality of Service (QoS) support | ✔ |
| Universal Plug and Play (UPnP) | ✔ |
| **Ports & interfaces** | |
| Ethernet LAN (RJ-45) ports * | 4 |
| **Protocols** | |
| DHCP client * | ✔ |
| DHCP server * | ✔ |
| Supported network protocols | SNMP, HTTP |
| **Security** | |
| Security algorithms * | 3DES, DES |
| MAC address filtering | ✔ |
| VPN tunnels quantity | 50 |
| **Packaging content** | |
| Manual | ✔ |
| Quick start guide | ✔ |
| User Guide on CD-ROM | ✔ |
| **Features** | |
| Flash memory | 16 MB |

| Features | |
|---|---|
| Plug and Play | ✔ |
| Mean time between failures (MTBF) | 90000 h |
| Certification | EN55022 A, FCC A, VCCI A, AS/NZS CISPR22 A, EN55024, UL60950, CAN/CSA-C22.2NO. 60950-00, EN60950, UL, cUL,TUV |
| Minimum processor | 266 MHz |
| Minimum RAM | 32 MB |
| **Design** | |
| LED indicators | ✔ |
| **Operational conditions** | |
| Operating temperature (T-T) | 0 - 40 °C |
| Storage temperature (T-T) | -25 - 70 °C |
| Operating relative humidity (H-H) | 5 - 95% |
| **Weight & dimensions** | |
| Weight | 1.75 kg |
| **Other features** | |
| Maximum data transfer rate | 0.1 Gbit/s |
| Dimensions (WxDxH) | 305 x 190 x 45 mm |
| Compatible operating systems | Windows XP, 2000 |
| Connectivity technology | Wired |
| Connectivity LEDs | ✔ |
| Mac compatibility | ✘ |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-APR-2025. Prints or copies of Information are only valid on the printed Publication date