

HP ProLiant SL390s G7 Intel® 5520 Socket B (LGA 1366) Rack (4U) Màu đen, Màu xám

Nhãn hiệu : HP

Mã sản phẩm: 612228-B21

Tên mẫu : ProLiant SL390s G7

HP ProLiant SL390s G7. Chipset bo mạch chủ: Intel® 5520, Đầu cắm bộ xử lý: Socket B (LGA 1366), Họ bộ xử lý: Intel. Hỗ trợ các kích thước DIMM: 16GB, 4GB, Bộ nhớ RDIMM tối đa: 192 GB, Bộ nhớ UDIMM tối đa: 48 GB. Kích cỡ ổ lưu trữ được hỗ trợ: 2.5", Chuẩn giao tiếp ổ cứng lưu trữ được hỗ trợ: Serial Attached SCSI (SAS), SATA, Bộ điều khiển lưu trữ: HP Smart Array B110i. Bộ nhớ điều hợp đồ họa tối đa: 64 MB. Loại chuẩn giao tiếp Ethernet: Fast Ethernet, Gigabit Ethernet, Tốc độ truyền dữ liệu mạng cục bộ (LAN) Ethernet: 10,100,1000 Mbit/s, Công nghệ cáp đồng ethernet: 1000BASE-T, 1000BASE-TX, 100BASE-TX, 100BASE-T



Processor		Network	
Motherboard chipset *	Intel® 5520	Ethernet LAN data rates	10,100,1000 Mbit/s
Processor socket * Processor family	Socket B (LGA 1366) Intel	Copper ethernet cabling technology	1000BASE-T, 1000BASE-TX, 100BASE-TX, 10BASE-T
Number of processors supported *	2	Ports & interfaces	
Supported processor frequency (max)	3.6 GHz	USB 2.0 ports quantity * Ethernet LAN (RI-45) ports *	3 2
Compatible processor series	Intel® Xeon®	VGA (D-Sub) ports quantity	1
Intel Xeon series	E5500, E5600, L5600, X5600	Serial ports quantity	1
Memory		Expansion slots	
Number of DIMM slots * Supported DIMM module capacities Maximum RDIMM memory	12 16GB, 4GB 192 GB	PCI Express slots version PCI Express x8 slots PCI Express x16 slots	2.0 1 8
Maximum UDIMM memory	48 GB		0
Supported RDIMM clock speeds	800,1066,1333 MHz	Features	
Supported UDIMM clock speeds	800,1066,1333 MHz	Optical drive type	×
ECC Storage	<i>•</i>	Compatible operating systems	Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESX
Number of storage drives supported *	8	Design	
Storage drive sizes supported	2.5"	Chassis type *	Rack (4U)
Supported storage drive interfaces	Serial Attached SCSI (SAS), Serial ATA HP Smart Array B110i 0, 1, 10	Product colour	Black, Grey
		Power	
Storage controller RAID levels		AC input voltage AC input frequency	90 - 264 V 47 - 63 Hz
Graphics			47 03 112
Maximum graphics card memory	64 MB	Operational conditions	10. 25.00
Network		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	10 - 35 °C -30 - 60 °C
Ethernet interface type	Fast Ethernet, Gigabit Ethernet		10 - 90% 5 - 95%
		Other features	

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.